

Tiger Neo N-type 54HL4R-B 425-445 Watt

N-Type

ALL-BLACK MODULE

Positive power tolerance of 0~+3%


IEC61215(2016), IEC61730(2016)

ISO9001:2015: Quality Management System

ISO14001:2015: Environment Management System

ISO45001:2018

Occupational health and safety management systems



Key Features



SMBB Technology

Better light trapping and current collection to improve module power output and reliability.



Hot 2.0 Technology

The N-type module with Hot 2.0 technology has better reliability and lower LID/LETID.



PID Resistance

Excellent Anti-PID performance guarantee via optimized mass-production process and materials control.



Enhanced Mechanical Load

Certified to withstand: wind load (4000 Pascal) and snow load (6000 Pascal).




Durability Against Extreme Environmental Conditions

High salt mist and ammonia resistance.



LINEAR PERFORMANCE WARRANTY






25 30 Year Product Warranty

0.40% Year Linear Power Warranty

Annual Degradation Over 30 years

Engineering Drawings



Packaging Configuration

(Two pallets = One stack)

36pcs/pallets, 72pcs/stack, 936pcs/ 40'HQ Container

Mechanical Characteristics

Cell Type	N type Mono-crystalline
No. of cells	108 (6×18)
Dimensions	1762×1134×30mm (69.36×44.65×1.18 inch)
Weight	22 kg (48.50 lbs)
Front Glass	3.2mm, Anti-Reflection Coating, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Output Cables	TUV 1×4.0mm (+): 400mm, (-): 200mm or Customized Length

SPECIFICATIONS

Module Type	JKM425N-54HL4R-B		JKM430N-54HL4R-B		JKM435N-54HL4R-B		JKM440N-54HL4R-B		JKM445N-54HL4R-B	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax)	425Wp	320Wp	430Wp	323Wp	435Wp	327Wp	440Wp	331Wp	445Wp	335Wp
Maximum Power Voltage (Vmp)	32.37V	30.19V	32.58V	30.30V	32.78V	30.50V	32.99V	30.73V	33.19V	30.93V
Maximum Power Current (Imp)	13.13A	10.60A	13.20A	10.66A	13.27V	10.72A	13.34A	10.77A	13.41A	10.83A
Open-circuit Voltage (Voc)	38.95V	37.00V	39.16V	37.20V	39.36V	37.39V	39.57V	37.59V	39.77V	37.78V
Short-circuit Current (Isc)	13.58A	10.96A	13.65A	11.02A	13.72A	11.08A	13.80A	11.14A	13.87A	11.20A
Module Efficiency STC (%)	21.27%		21.52%		21.77%		22.02%		22.27%	
Operating Temperature(°C)						-40°C~+85°C				
Maximum system voltage						1000VDC (IEC)				
Maximum series fuse rating						25A				
Power tolerance						0~+3%				
Temperature coefficients of Pmax						-0.29%/°C				
Temperature coefficients of Voc						-0.25%/°C				
Temperature coefficients of Isc						0.045%/°C				
Nominal operating cell temperature (NOCT)						45±2°C				

*STC: Irradiance 1000W/m²

 Cell Temperature 25°C

 AM=1.5

NOCT: Irradiance 800W/m²

 Ambient Temperature 20°C

 AM=1.5

 Wind Speed 1m/s

PRO·BAT

Pro-bat d.o.o, IOC Zapolje III 8, SI-1370 Logatec, Slovenia

Tel:030 336-086 mail.info@pro-bat.si, www.pro-bat.si

JKM425-445N-54HL4R-B-F2-EN